

# FSA LOG ROLL CUTTER



**Application :** Suitable for cutting masking, double side, foam & cloth tapes...etc.

**Specification :**

Machine Width :	1.0M/1.3M/1.6M	Max. Cutting O.D :	400mm
Cutting Core O.D :	26mm – 77mm (1”– 3”)	Min. Cutting Width :	2mm

**Feature :**

1. Cutting shaft and circular blade are driven by A.C motor with inverter control, which is able to set RPM and running direction obverse/reserve on different requests.
2. Width setting is controlled by servo motor with ball screw and guide rails to make accuracy movement.
3. All functions are operated under LCD touch panel control, which is operator friendly and easy for data setting.
4. Central control system is as PLC unit, in which has materials cutting memory mode and all of electrical devices are compliant to the latest European CE regulation for safety operation.
5. Knife feeding is controlled by servo motor, the cutting speed is adjustable in 3 stages.
6. Equipped with knife angle auto adjustment by servo motor control, cutting angle can be changed from -9 to +9 degree automatically for making roll surface smoothly.
7. Laser lighting device to position the first cut on the log roll easily and quickly.
8. Slide move type safety cover to protect operator during the production, which is comply with the CE regulation.

**Optional Parts :**

1. Other Size Cutting Shaft : It can be made as per required core I.D.
2. Cutting Supporter : For supporting log roll when cutting core below 38mm.
3. Air Type Cutting Shaft : To improve cutting accuracy when the tolerance of paper core I.D is too big.
4. Sharpening Device : Grinding knife on the machine to save time for taking blade off.



Adress  
Phone  
Fax  
Email  
Website

De Hoogjens 48 4254 XW Sleenwijk  
+31 (0)183 – 600810  
+31 (0)183 – 600753 Email  
[info@ehw-elektro.nl](mailto:info@ehw-elektro.nl)  
[www.ehw-elektro.nl](http://www.ehw-elektro.nl)