



**Application:** Shaftless surface type winding, suitable for rewinding masking, PET, PE, cloth tapes and films,

papers...etc.

Specification: Machine Width: 1.0M/1.3M/1.6M Max. Unwind O.D: 800mm

Rewind Core I.D: 26-77mm (1" - 3") Max. Rewind O.D: 200mm

Machine Speed: 120M / Min

## Feature:

- 1. Equipped with the connected unwind base, which is convenience on operation and space saving.
- 2. Equipped auto tension controller and surface type lay on roller on unwind base to make web wound out smoothly.
- 3. Driven by one A.C motor with 2 stages type length counter to make machine stops accurately.
- 4. Surface type winding able to press air out of log roll, and shaftless design can rewind any sizes of paper cores without changing machine parts.
- 5. Rewind tension is as clutch controls surface pressure roller, the tension is adjustable on different requests.
- 6. Central control system is as PLC unit and all of electrical devices are compliant to the latest European CE regulation for safety operation.

## **Optional Parts:**

1. Unwind Pick-Up Lift: For loading jumbo roll on the machine quickly and time saving.

2. Tabbing Device : Automatic tabbing on the web during the production.

3. Noise Reduction Hood: For attenuating the production sound when the machine is running.



Adress Phone Fax Email Website De Hoogjens 48 4254 XW Sleeuwijk +31 (0)183 – 600810 +31 (0)183 – 600753 Email info@ehw-elektro.nl www.ehw-elektro.nl