

# EPT SLITTER



**Application :** 2 shafts center-surface type winding, suitable for slitting/rewinding various adhesive tapes.

**Specification :**

Machine Width :	1.0M/1.3M/1.6M	Max. Unwind O.D :	1000mm
Rewind Core I.D :	77mm	Min. Slitting Width :	10mm (as per rewind O.D)
Max. Rewind O.D :	600mm	Machine Speed :	200M / Min

**Feature :**

1. Equipped with separated shaft type unwind base, auto web guide and auto unwind tension controller.
2. On this model, the distance from slitting device to rewind section is so short, which is suitable to do narrow sizes slitting and carry out perfect winding on all finished rolls.
3. Driven by connective 3 A.C motors, 1 for web feeding, 2 for rewind tension control which automatically increasing torque on the rewind shafts when the finished roll O.D is getting bigger.
4. Center-surface type winding, horizontal control on rewind shaft arm is by air automatic adjustable, contacting pressure can be set on request.
5. Central control system is as PLC unit with LCD touch panel, which has friendly operation for all data setting.
6. Slitting by shear cutter, air score knife and razor blade, which were designed for multi-purpose materials cutting.

**Optional Parts :**

1. Unwind Pick-Up Lift : For loading jumbo roll on the machine quickly and time saving.
2. Finished Rolls Crane : For lifting rewind shafts and unloading finished rolls.
3. Noise Reduction Hood : For attenuating the production sound when the machine is running.
4. Special Unwind Base : Separated type with shaftless hydraulic core chuck can be equipped for efficient and quick performance on jumbo roll change.



Address  
Phone  
Fax  
Email  
Website

De Hoogjens 48 4254 XW Sleeuwijk  
+31 (0)183 – 600810  
+31 (0)183 – 600753 Email  
[info@ehw-elektro.nl](mailto:info@ehw-elektro.nl)  
[www.ehw-elektro.nl](http://www.ehw-elektro.nl)